



PEGASUS

W674 series

4 or 5-needle, cylinder bed, double chainstitch machines for super tucking

“Super tuckers” are added to the W600 series


Can **insert, attach and/or hem elastic** neatly and uniformly with ease operation.

For inserting elastic on waists of tubular goods

W674-40CC / W674-45CC (with under fabric trimmer)


(Seam type: A)

For hemming waists and simultaneously inserting three or four elastic rings into medium weight tubular goods.



(Seam type: C)



For hemming waists and simultaneously inserting flat elastic rings into waistbands of light to medium weight tubular goods.



For attaching elastic on waists of tubular goods

W674-42C (Seam type: E)


For attaching flat elastic rings to waists.



For hemming elastic on waists of tubular goods

W674-42C (Seam type: F)

For hemming flat elastic rings pre-attached to waists by overedgers.



The photo above shows the W674-40CC series.



Features

- **Inserts, hems and attached elastic easily and neatly into/on waists of medium weight fabrics such as jogging trunks and sweat pants.**
- **With a full range of subclasses, you can select as required according to your needs.**


Display cases

W674 - ¹40 ²C ³C X ⁴4 ⁵308 ⁶A ⁷01

- 1 Subclass**
40 : 406+401+401
406+401+401+401
42 : 401+401+401+401
45 : 406+401+401 (With underbed fabric trimmer)
406+401+401+401 (With underbed fabric trimmer)
- 2 Gauge parts**
- 3 Type of needle plate finger**
A : Suitable for the fine stitch length (1.7 mm or less)
B : For standard stitch length (1.8 - 2.3 mm)
C : Suitable for the coarse stitch length (2.5 mm or more)
- 4 No. of needles**
- 5 Needle space**
Ex) 4.8+13+13=30.8
- 6 Seam style**
- 7 Needle space pitch (mm)**
01 : 4.8-13-13 06 : 4.8-10-10-10
02 : 5.6-13-13 07 : 6.4-6.4-6.4-6.4
03 : 4.8-10-10 08 : 10-10-10
04 : 5.6-10-10 09 : 6.4-6.4-6.4
05 : 8.5-8.5-8.5 10 : 4.8-13-13-13
11 : 5.6-13-13-13

W674 series subclasses

									Accessories / Option / Remarks
① ② ③ For inserting elastic or waists of tubular goods		W674-40CCx4308A01	4	7	4.8×13×13	4.5	8	4,000	Accessories : HG,RP Option : UT
		W674-40CCx4316A02			5.6×13×13				
		W674-40CCx4248A03			4.8×10×10				
		W674-40CCx4256A04			5.6×10×10				
		W674-40CCx5348A06	5	9	4.8×10×10×10				
		W674-40CCx5438A10			4.8×13×13×13				
		W674-40CCx5446A11			5.6×13×13×13				
		W674-45CCx4308A01			4.8×13×13				
		W674-45CCx4316A02	4	7	5.6×13×13				
		W674-45CCx4248A03			4.8×10×10				
		W674-45CCx4256A04			5.6×10×10				
		W674-45CCx5348A06			4.8×10×10×10				
W674-45CCx5438A10	5	9	4.8×13×13×13						
W674-45CCx5446A11			5.6×13×13×13						
④ For attaching elastic or waists of tubular goods		W674-42Bx4255E05	4	8	8.5×8.5×8.5	4.5	8	4,000	Accessories : RP Option : UT
		W674-42Cx4300E08			10×10×10				
⑤ For hemming elastic or waists of tubular goods		W674-42Bx4255F05	4	8	8.5×8.5×8.5	4.5	8	4,000	Accessories : RP Option : UT
		W674-42Bx4192F09			6.4×6.4×6.4				
		W674-42Cx4300F08			10×10×10				



PEGASUS CO., LTD.

5-7-2 Sagisu Fukushima-ku, Osaka 553-0002 Japan
TEL : +81-6-6458-4739 FAX : +81-6-6454-8785

-Specifications and appearance are subjected to changes without notice.
-Read the instruction manual before operating the machine to ensure safe usage.
-Photos for illustration purpose. They may not represent actual operating conditions and/or displayed optional parts.

©2015 PEGASUS CO., LTD.
Catalog No. 102962① January 2024

